



CARACTERISTICI L'ALTRA-PIETRA-CATTEDRALE		CARACTERISTICI TEHNICE	STANDARD	LIMITE STABILITE		L'ALTRA PIETRA®
REGULARITATE		LUNGIME SI LATIME	ISO 10545-2	± 0.6 %	± 2 mm	CONFORM
		GROSIME	ISO 10545-2	± 5.0 %	± 0,5 mm	CONFORM
		RECTANGULARITATE	ISO 10545-2	± 0.5 %	± 2 mm	CONFORM
		RECTITUDINEA LATURILOR	ISO 10545-2	± 0.5 %	± 1,5 mm	CONFORM
		PLATITUDINEA SUPRAFEȚEI	ISO 10545-2	± 0.5 %	± 2 mm	CONFORM
STRUCTURA		ABSORBTIE APA	ISO 10545-3	≤ 0.5 %		< 0.1 %
		REZISTENTA LA RUPERE	ISO 10545-4	≥ 1300 N		≥ 10000 N
		MODULUL DE RUPERE	ISO 10545-4	≥ 35 N/mm²		≥ 35 N/mm²
TERMO-HIGROMETRIC		DILATARE TERMICA LINIARA	ISO 10545-8	VALOARE DECLARATA		< 7x10 ⁻⁶ °C ⁽⁻⁾ (1)
		REZISTENTA LA SOC TERMIC	ISO 10545-9	TEST VALID		GARANTAT
		REZISTENTA LA INGHET	ISO 10545-12	TEST VALID		GARANTAT
CHIMIC		REZISTENTA LA SUBSTANTE CHIMICE	ISO 10545-13	UB MINIM		GARANTAT
		REZISTENTA LA PETE	ISO 10545-14	≥ 3		GARANTAT

PIATRA ONLINE

021 9907 / office@piatraonline.ro

Aleea Teisani nr.137A, sector 1, 014034 Bucuresti

SIGURANTA		REZISTENTA LA DERAPAJ	DIN 51130	VALOARE DECLARATA	R11
			DIN 51097		A+B

In conformitate cu standardele EN 14411 (ISO 13006) anexa G